

TECHNICAL DATA SHEET

Vagus MTAf - Silver

1. Description

Printable Silvery Vinyl

Film : 90 micron Silver PET aluminized film;

Adhesive : Removable Transparent Adhesive;

Release liner : 125mic PET;

Width : 1.27/1.37/1.52m;

2. Properties

Testing condition: Indoor temperature 23±2°C,Relative Humidity 50±5%.

Test tools like Aluminum plate, glass, steel plate are used for below testing

Item	Unit	Value	Tested Method
Thickness PET	Micron	70±10	GB/T6672-2001
Weight-Liner	g/m ²	175±10	GB4669-1995
Weight-finished product	g/m ²	295±20	GB4669-1995
Gloss Rate 60°	%	≥70	GB8807-88
Initial adhesive 24h	N/25mm	≥8	FTM 9
180°peel Dimensional	N/25mm	≥5	FTM 1
Dimensional stability MD	mm	≤0.8	FTM 14
Dimensional stability CD	mm	≤0.5	FTM 14
Tensile strength MD	N/25mm	≥45	GB/T1040.1-2006
Tensile strength CD	N/25mm	≥40	GB/T1040.1-2006
Construction Temperature	°C	20±10°C	
Applicable Temperature	°C	-20 ~ +70	

3. Features

- Fully compatible and suitable for various printer models;
- The spray-painted picture is clear, with saturated colors, fast-drying ink, and no ink smearing;
- The aluminized film has excellent metallic gloss, with a light reflectivity of more than 92%.;
- The aluminized film also possesses appropriate aging resistance.

4. Applications

1. Mobile media, commercial billboard advertisements, signs, exhibition displays,
2. Suitable for solvent, eco-solvent, HP Latex and UV ink printing.

5. Shelf Life and Storage

Activity	Recommendations
Storage conditions	<ul style="list-style-type: none"> • All VAGUS products always need to be stored in the original packing and with the original protection materials, preferably stored hermetically, no more than 6 layers if stored horizontally. Do not expose in direct sunlight or heat sources. Shelf life will be one year with temperature of $25^{\circ}\text{C}\pm 5^{\circ}\text{C}$ and relative humidity of $50\pm 15\%$.
Production and Application Environment:	<ul style="list-style-type: none"> • Production environment: temperature of $25\pm 5^{\circ}\text{C}$, relative humidity of $50\%\pm 10\%$, clean dust-free environment without suspended matter; Please move the materials to the printing environment 24 hours before printing. Test prior to use and remain enough edge margins when printing.

6. Warranty Condition

- One year shelf life: stored in suitable conditions, preferably use within six months. Quality range is only for ink adsorption, other physical parameter is only for reference.
- One year prosecution period: from the product manufacture date, no-acceptance for overdue product.

Declaration: Please choose VAGUS products suitably according to relative provisions or industrial standards. VAGUS bears the responsibility for the specified technical and performance data on this page only. VAGUS is not responsible for any other liability. (The technical data on this page is calculated on average, and $\pm 5\%$ tolerance is acceptable)