

Technical Data Sheet ENVIRO FL110ST

Whiteback Frontlit Fabric

Application

Flags, Banners, Poster

Technical Specifications

Base Material	100% Polyester	DIN 60001,ASTM D7641
Yarn	125D*150D	DIN EN 2060,ASTM D1907
Weave Method	Woven	---
Weight	110±10gsm	ISO536
Thickness	160±30 µm	ISO534
Opacity	≥ 75%	ISO2471
Whiteness	90± 10	ISO11475
Color	L*: 90.0±2.0; a*: 1.0±2.0; b*: -3.0±2.0	---
Gloss [60°]	5±2	---
Flame Resistance	NO	---

Size

Width	0.914 m/1.118 m/1.37 m/1.524 m/1.60 m/2.60 m/3.20 m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	100 m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection.

It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

